

## WINDOW TKT 2+1

### Description:

Double-frame inwards opening wood- aluminium window

### Performance characteristics:

Air permeability: class 4  
Resistance to wind load: class C4  
Water tightness: class E1050

\* tested window dimensions (width x height) 1230 mm x 1480 mm

### Technical data:

Wood material: Pine with class J10 according to standard EN 942. All wooden details are impregnated in the unit FLOWCO-ROLL with wood protection treatment INDULINE SW-900.

Glass: Double insulated glass unit in inner sash, thickness up to 24 mm and up to 8 mm glass in outer sash. Glazing and window configurations can achieve soundproofing up to 48 dB.

Glazing: Plastic glazing bar in standard.

Gasket: The basic two-chamber gasket with silicone rubber seal. In addition, the outer sheathing frame and two-frame gasket. Sealant color grey.

Finishing: White in standard

Fittings: G.U UNI-JET

Handle: Hoppe

Module dimensions: External dimension of frame= dimension of wall opening – 20 mm



Height	Width															
	4	5	6	7	8	9	10	11	12	13	14	15	16			
5	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
6	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
7	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
8	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
9	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
10	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
11	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
12	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
13	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
14	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
15	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
16	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
17	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
18	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
19	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
20	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK
21	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK

Orange	Pieces are too short for line production
Green	OK
Yellow	Difficulties to open window
Pink	Support window if needed to open



Drawings:

